

Dimensions and weight

Height:	17 mm (0.66 in)
Width	357 mm (14.06 in)
Depth	235 mm (9.27 in)
Weight (minimum):	
Touch	2 kg (4.41 lb)
Non-touch	1.78 kg (3.93 lb)
	NOTE : The weight of your laptop varies depending on the configuration ordered and the manufacturing variability.
	Lapton VANG.C



System information

Computer model

Processor

Chipset

XPS 9550

- 6th Generation Intel Core i3
- 6th Generation Intel Quad Core i5
- 6th Generation Intel Quad Core i7
- Mobile Intel HM170 Express Chipset
- Intel CM236

Laptop VANG. com





Memory

Slots	Two SODIMM slots
Туре	DDR4
Speed	2133 MHz
Configurations supported	8 GB, 16 GB, and 32 GB





Ports and connectors

External:		
USB	Two USB 3.0 ports with PowerShare	
	 One Thunderbolt 3 port with PowerShare (USB-C) 	
Audio/video	One HDMI 1.4 port	
	 One headset port (headphone and microphone combo) 	
Internal:		
M.2	One M.2 card slot for Wi-Fi and Bluetooth combo card	





Communications

Wireless

- Wi-Fi 802.11ac
- Wi-Fi 802.11a/g/n
- Bluetooth 4.1
- Intel WiDi (optional)





Video

Controller: Discrete

Integrated

Memory:

Discrete

Integrated

NVIDIA GeForce GTX 960M Intel HD Graphics 530

Up to 2 GB GDDR5 Shared system memory





Audio

Controller	Realtek ALC3266 with Waves MaxxAudio Pro
Speakers	Two
Speaker output:	
Average	2 W
Peak	2.5 W
Microphone	Dual array-microphones
Volume controls	Media-control shortcut keys and volume-control buttons

nonce.





Storage Interface

Hard drive

Solid state drives (optional)

•	SATA 3	Gbps

• SATA 6 Gbps

• PCIE Gen 3

One 2.5-inch drive (supports Intel Smart Response Technology) One Solid State Drive (SSD) with Intel Smart Cache support



Media-card reader

Туре

Card supported

One 6-in-1 slot

- SD card
- SD High-Capacity (SDHC) card
- SD Input Output (SDIO) card
- SD Extended Capacity (SDXC)
- SD Extended Capacity (SDXC) card with Ultra High Speed (UHS)
- Multimedia card (MMC) with Ultra High Speed (UHS)







Display

Туре	• 15.6-inch FHD	
	 15.6-inch UltraHD 	
	FHD	UltraHD
Resolution (maximum)	1920 x 1080	3840 x 2160
Dimensions:		
Height	194.50 mm (7.66 in)	194.50 mm (7.66 in)
Width	345.60 mm (13.61 in)	345.60 mm (13.61 in)
Diagonal	396.52 mm (15.61 in)	396.52 mm (15.61 in)
Refresh rate	60 Hz	60 Hz
Operating angle	0 degree (closed) to 135 degrees	0 degree (closed) to 135 degrees
Pixel pitch	0.18 mm	0.09 mm
Controls	Brightness can be controlled using keybo	ard shortcuts keys.





Keyboard

Туре

Shortcut keys

Backlit keyboard

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.

NOTE: You can change the behavior of the shortcut keys by pressing Fn+Esc or by changing **Function Key Behavior** in BIOS setup program.

eys. List of shortcut keys.





Camera

Resolution:

Still image

Video (maximum)

Diagonal viewing angle

1280 x 720 megapixels 1280 x 720 (HD) at 30 fps 74 degrees





Touch pad

Resolution:	
Horizontal	1273 dpi
Vertical	1217 dpi
Dimensions:	
Width	105 mm (4.13 in)
Height	80 mm (3.15 in)

LaptopVANG.com





Battery

Туре	3-cell (56 WHr)	6-cell (84 WHr)
Dimensions:		
Width	71.80 mm (2.83 in)	71.80 mm (2.83 in)
Lenght	223.20 mm (8.79 in)	330.50 mm (13.01 in)
Height	7.20 mm (0.28 in)	7.20 mm (0.28 in)
Weight (maximum)	0.54 lb (0.24 kg)	0.76 lb (0.34 kg)
Voltage	11.4 VDC	11.4 VDC
Charging time (approximate)	4 hours when the computer is off	
Operating time	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions	
Life span (approximate)	300 discharge/charge cycles	300 discharge/charge cycles
Temperature range:		
Operating	0°C to 35°C (32°F to 95°F)	0°C to 35°C (32°F to 95°F)
Storage	–40°C to 65°C (–40°F to 149°F)	–40°C to 65°C (–40°F to 149°F)
Coin-cell battery	ML1220	
	NOTE : It is recommended that you use a Dell coin-cell battery for your computer. Dell does not provide warranty coverage for problems caused by using accesories, parts, or components not supplied by Dell.	

Battman capable



Yes

Yes



Power adapter

Туре	130 W
Input voltage	100 VAC-240 VAC
Input frequency	50 Hz-60 Hz
Input current (maximum):	1.80 A
Output current (maximum):	6.67 A
Rated output voltage	19.50 VDC
Temperature range:	
Operating	0°C to 40°C (32°F to 104°F)
Storage	–40°C to 70°C (–40°F to 158°F)



Computer environment

Airborne contaminant level	G1 as define
	Operating
Temperature range	0°C to 40°C
Relative humidity (maximum)	10% to 90%
Vibration (maximum)*	0.66 GRMS
Shock (maximum)	110 G [†]
Altitude (maximum)	–15.2 m to 3 (–50 ft to 10

A1 as defined by ISA-S71.04-1985 **Operating** I°C to 40°C (32°F to 104°F) 0% to 90% (non-condensing) 0.66 GRMS 10 G[†] -15.2 m to 3048 m -50 ft to 10,000 ft)

Storage

-40°C to 70°C (-40°F to 158°F) 10% to 95% (non-condensing) 1.30 GRMS 160 G[‡] -15.2 m to 10,668 m (-50 ft to 35,000 ft)

* Measured using a random vibration spectrum that simulates user environment.

† Measured using a 2 ms half-sine pulse when the hard drive is in use.

‡ Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.

