ThinkPad T470 Platform Specifications

Processor

Optical

WI AN

Ethernet

Bluetooth™

None

vPro model:

M.2 card

| | Number | # of Cores | # of Threads | Frequency | Frequency | Cache | Types | Graphics | | | |
|-------------------|---|---------------|-----------------|-------------|----------------|------------|-----------|--------------------------|--|--|--|
| | i5-6200U | 00.00 | 11110440 | 2.3 GHz | 2.8 GHz | змв | .,,,,, | Intel LID Craphics | | | |
| | i5-6300U | 2 | 4 | 2.4 GHz | 3.0 GHz | 3MB | DDR4-2133 | | | | |
| | i7-6500U | | | 2.5 GHz | 3.1 GHz | 4MB | | | | | |
| | i7-6600U | | | 2.6 GHz | 3.4 GHz | 4MB | | | | | |
| | 7th Generation Intel Core i3 / i5 / i7 Processor | | | | | | | | | | |
| | Processor | # of | # of | Base | Max Turbo | Cache | Memory | Processor | | | |
| | Number | Cores | Threads | Frequency | Frequency | Cacrie | Types | Graphics | | | |
| | i3-7100U | 2 | 4 | 2.4 GHz | - | 3MB | DDR4-2133 | Intel HD Graphics 620 | | | |
| | i5-7200U | | | 2.5 GHz | 3.1 GHz | 3MB | | | | | |
| | i5-7300U | | | 2.6 GHz | 3.5 GHz | 3MB | | | | | |
| | i7-7500U | | | 2.7 GHz | 3.5 GHz | 4MB | | | | | |
| | i7-7600U | | | 2.8 GHz | 3.9 GHz | 4MB | | | | | |
| | * i7-6500U is NOT available in EMEA | | | | | | | | | | |
| Graphics | Intel HD Graphics 520 or 620 in processor only, or Intel HD Graphics 620 in processor and NVIDIA GeForce® 940MX, 2GB 2.5GHz GDDR5 memory (discrete models are NOT available in EMEA); supports external digital monitor via HDMI or USB Type-C; supports three independent displays; Max resolution: 4096x2304@60Hz (USB Type-C); 4096x2160@24Hz (HDMI) | | | | | | | | | | |
| Chipset Memory | Intel SoC (System on Chip) platform, 32GB max / 2400MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets * System clocks down for processors with lower memory controller | | | | | | | | | | |
| Display | Some: 14.0" (355mm) HD (1366x768), anti-glare, LED backlight, 220 nits, 16:9 aspect ratio, 400:1 contrast ratio Some: 14.0" (355mm) FHD (1920x1080), anti-glare, LED backlight, 220 nits, 16:9 aspect ratio, 400:1 or 500:1 contrast ratio Some: 14.0" (355mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle | | | | | | | | | | |
| Multi-touch (opt) | On-cell touch, supports 10-finger gesture (FHD IPS panel with PPS cover only) | | | | | | | | | | |
| Storage | System has | one Hi | DD slot or | one M.2 228 | 30 slot exclus | sively for | storage | | | | |

Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD)

Intel Tri-Band Wireless-AC 18265, WiGia 802,11ad + Wi-Fi 2x2 802,11ac + BT4.1.

Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s

mutually exclusive with WWAN and WiGig

Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville)

Realtek® RTL8822BE, Wi-Fi 2x2 802,11ac + BT4.1, M.2 card

Bluetooth 4.1 wireless, integrated in Wi-Fi + Bluetooth combo adapter * Intel 8265ac / 18265ac card support BT4.2 but is limited to BT4.1 by Windows OS

Processor # of # of Base May Turbo

6th Generation Intel® Core™ i5 / i7 Processor or

Some: 128GB M.2 SSD / SATA 6.0Gb/s, in WWAN slot as 2nd Storage, Intel Ethernet Connection I219-LM (Jacksonville) One of the following, configurable by model (WiGig can coexist with WWAN):

Intel Dual Band Wireless-AC 8260, Wi-Fi 2x2 802.11ac + BT4.1, M.2 card
 Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + BT4.1, M.2 card

| WWAN (optional) | One of the following, configurable by model (WWAN can coexist with WiGig): Wireless WAN upgradable Integrated Mobile Broadband 4G LTE-A, One of the following, configurable by model (WWAN can coexist with WiGig): | | | | | | | | | | |
|--|--|---|--|---------------|-----------------|-----------------|--|--|--|--|--|
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | Qualcomm® Snapdragon™ X7 LTE-A (Sierra Wireless EM7455), M.2 card • Integrated Mobile Broadband 4G LTE, | | | | | | | | | | |
| | | | (Fibocom L831-EAU), M.2 card (EMEA only) | | | | | | | | |
| SIM card (opt) | Micro-SIM card slot, opt Verizon LTE (US) or Lenovo® Connect (EMEA) SIM card | | | | | | | | | | |
| Dimensions Weight | <i>WxDxH:</i> 13.25" x 9.15" x 0.79"; 336.6mm x 232.5mm x 19.95mm | | | | | | | | | | |
| | Models | 3-cell or 3 + 3-cell 6-cell or 3 + 6-cell | | | | | | | | | |
| | Magnesium | 3.49 lb / 1 | | 3.92 lb / 1 | | | | | | | |
| | PPS | 3.63 lb / 1 | 1.65 kg | 4.35 lb / 1 | .85 kg | | | | | | |
| Case color | Black | | | | | | | | | | |
| Case material | Display cover: Magnesium Hybrid or PPS; Bottom: Glass-Fiber Reinforced Plastic | | | | | | | | | | |
| Smart card reader Optional: Smart card reader | | | | | | | | | | | |
| Media reader 4-in-1 reader (MMC, SD, SDHC, SDXC), supports SD 3.0, UHS-I | | | | | | | | | | | |
| Ports | Three USB 3.1 Gen 1 (USB 3.0, one Always On), | | | | | | | | | | |
| | USB 3.1 Type-C Gen 2 / Thunderbolt 3 (w/ the function of Power Delivery and DP). | | | | | | | | | | |
| | HDMI 1.4b, Ethernet (RJ-45), Dock connector * Depending on many factors, actual data transfer speed may be lower than theoretical speed | | | | | | | | | | |
| WiGig dock (opt) | | | | | | | | | | | |
| Monitor cable | HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter | | | | | | | | | | |
| (optional) | | | | | | | | | | | |
| Camera (optional) 720p: HD720p resolution, fixed focus | | | | | | | | | | | |
| | <i>IR & 720p:</i> IR c | | | | | WiGig) | | | | | |
| Audio support | HD Audio, Realtek ALC3268 codec / stereo speakers, 2W x 2 / dual array microphone, combo audio/microphone jack | | | | | | | | | | |
| Keyboard | 6-row, spill-resistant, multimedia Fn keys, optional LED backlight | | | | | | | | | | |
| UltraNav™ | TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad | | | | | | | | | | |
| Security Power-on password, hard disk password, supervisor password, security ke | | | | | | | | | | | |
| Security chip vPro (optional) | Discrete TPM 1.2 or 2.0, TCG Certified Intel vPro Technology | | | | | | | | | | |
| Fingerprint reader | | | on chip fina | erprint reade | er on the keybo | ard bezel | | | | | |
| NFC (optional) | Near Field Com | | o opg | o. p | | | | | | | |
| Internal battery | Optional: Integ | grated Li-Poly | mer 3-cell (2 | 24Wh) | | | | | | | |
| External battery Max battery life (<i>MobileMark</i> ® 2014) | Li-Polymer 3-ce | ll <i>(24Wh)</i> or L | _i-ion 6-cell | (48Wh or 72 | Wh) | | | | | | |
| | Models 3-c | ell 3 + 3-cell | 6-cell 48Wh | 6-cell 72Wh | 3 + 6-cell 48Wh | 3 + 6-cell 72Wh | | | | | |
| | Integrated 6.9 | hr 13.9 hr | 13.9 hr | 20.9 hr | 20.9 hr | 27.1 hr | | | | | |
| | Discrete 6.9 | | 14.3 hr | 21.6 hr | 21.2 hr | 28.6 hr | | | | | |
| AC adapter | * Battery life varie 45W or 65W sli | | | | | nter | | | | | |
| | | | | 0344 030 1 | ype-o Ao adap |) lei | | | | | |
| Operating system One of the following, configurable by model: • Windows® 7 Professional 64 preinstalled | | | | | | | | | | | |
| | through downgrade rights in Windows 10 Pro 64 • Windows 10 Home 64 | | | | | | | | | | |
| | | | | | | | | | | | |
| | Windows 10 | Pro 64 | | | | | | | | | |
| Limited warranty One of the following, configurable by model: | | | | | | | | | | | |
| | 1-year depot repair service 1-year depot with 2-year quotem board repair service | | | | | | | | | | |
| | 1-year depot with 2-year system board repair service 1-year limited onsite service 3-year/1-yr battery depot repair service | | | | | | | | | | |
| | | | | | | | | | | | |
| 3-year/1-yr battery limited onsite service | | | | | | | | | | | |
| | | | | | | | | | | | |

 Mil-Spec test
 MIL-STD-810G military testing

 Environment
 EPEAT™ Gold (US only); ENERGY STAR® 6.1; RoHS-compliant

Note: The specifications above may not be available in all regions.

Lenovo
February 2020