

OVERVIEW



1. SD card reader	7. Headphone / microphone combo jack (3.5mm)
2. USB 3.2 Gen 1	8. Ethernet (RJ-45)
3. Kensington Security Slot	9. USB-C 3.2 Gen 1
4. HDMI 2.0	10. 2x USB-C 3.2 Gen 2 / Thunderbolt 3
5. USB 3.2 Gen 1	11. Power connector
6. Nano-SIM card slot *	

Notes:

• Ports with * are only available on selected models



PERFORMANCE

Processor

Processor Family

10th Generation Intel® Core™ i5 / i7 / i9 Processor or Intel Xeon® W Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i5-10400H	4	8	2.6GHz	4.6GHz	8MB	DDR4-2933	Intel UHD Graphics
Core i7-10750H	6	12	2.6GHz	5.0GHz	12MB	DDR4-2933	Intel UHD Graphics
Core i7-10850H	6	12	2.7GHz	5.1GHz	12MB	DDR4-2933	Intel UHD Graphics
Core i7-10875H	8	16	2.3GHz	5.1GHz	16MB	DDR4-2933	Intel UHD Graphics
Core i9-10885H	8	16	2.4GHz	5.3GHz	16MB	DDR4-2933	Intel UHD Graphics
Core i9-10980HK	8	16	2.4GHz	5.3GHz	16MB	DDR4-2933	Intel UHD Graphics
Xeon W-10855M	6	12	2.8GHz	5.1GHz	12MB	DDR4-2933	Intel UHD Graphics
Xeon W-10885M	8	16	2.4GHz	5.3GHz	16MB	DDR4-2933	Intel UHD Graphics

Operating System

Operating System

- Windows® 10 Home 64
- Windows 10 Pro 64
- Windows 10 Pro 64 for Workstations
- Fedora Linux
- Red Hat Enterprise Linux (certified only)
- Ubuntu Linux LTS
- No operating system

Graphics

Graphics

 Windows® 10 Home 64 Windows 10 Pro 64 Windows 10 Pro 64 for Workstations Fedora Linux Red Hat Enterprise Linux (certified only) Ubuntu Linux LTS No operating system Graphics						
Graphics		apilo				
Graphics	Туре	Memory	Key Features			
NVIDIA® Quadro® T1000	Discrete	4GB GDDR6	DirectX® 12			
NVIDIA Quadro T2000	Discrete	4GB GDDR6	DirectX 12			
NVIDIA Quadro RTX 3000	Discrete	6GB GDDR6	DirectX 12			
NVIDIA Quadro RTX 4000 Max-Q	Discrete	8GB GDDR6	DirectX 12			
NVIDIA Quadro RTX 5000 Max-Q	16GB GDDR6	DirectX 12				

Monitor Support

Monitor Support

Supports up to 5 independent displays via native display and 4 external monitors; supports external monitors via HDMI® (up to 4K@60Hz), USB-C (up to 4K@60Hz) or Thunderbolt™ (one supports up to 5K@60Hz and the other supports up to 4K@60Hz)

Chipset

Chipset

Intel WM490 chipset

Memory

Max Memory[1]

Up to 128GB

Memory Slots

Four DDR4 SO-DIMM slots, dual-channel capable

Memory Type[2]



- DDR4-2933 ECC
- DDR4-2933 non-ECC

Memory Protection

ECC on models with ECC DIMMs and Xeon processor

Notes:

- 1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
- 2. Non-ECC memory is actually DDR4-3200 but may run at DDR4-2933 due to processor limitation

Storage

Storage Support

Up to two drives, 2x M.2 2280 SSD

• M.2 2280 SSD up to 2TB each

Storage Type

Disk Type	Interface	RPM	Security
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	Opal2

RAID

RAID 0/1 support

Removable Storage

Optical

None

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3286 codec

Speakers

Stereo speakers, Dolby® Atmos® Speaker System certified

Microphone

- · Dual array microphone, far-field
- No microphone

Camera

- 720p, with ThinkShutter, fixed focus
- IR & 720p hybrid, with ThinkShutter, fixed focus
- No camera

Battery

Battery

Integrated Li-Polymer 94Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 230W AC adapter

Max Battery Life[1]

MobileMark® 2014: 16.4 hr MobileMark 2018: 10.3 hr JEITA 2.0: 17.4 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, and/or JEITA 2.0 battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter

• 170W slim tip AC adapter (2-pin)



- 170W slim tip AC adapter (3-pin)
- 230W slim tip AC adapter (3-pin)

DESIGN

Display

Display^[2]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
15.6"	FHD (1920x1080)	None	IPS	500 nits	Anti-glare	16:9	1200:1	72% NTSC	160°	Dolby Vision™, HDR
15.6"	FHD (1920x1080)	None	IPS	300 nits	Anti-glare	16:9	700:1	72% NTSC	160°	-
15.6"	UHD (3840x2160)	Multi- touch	OLED	SDR 400nit, HDR 500nit (peak)	Anti- reflection Anti- smudge	16:9	100000:1	100% DCI- P3	170°	Dolby Vision, HDR
15.6"	UHD (3840x2160)	None	IPS	600 nits	Anti-glare	16:9	1400:1	100% Adobe® RGB	178°	Dolby Vision, HDR

Color Calibration

- X-Rite Pantone factory color calibration (UHD display)
- · No color calibration

Touchscreen

- · On-cell touch, supports 10-point touch
- · Non-touch

Notes:

- 1. California Electronic Waste Recycling Fee
 In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
 For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer
- 2. For non-OLED display, HDR is only supported under hybrid mode

Input Device

Pen

- Lenovo Pen Pro (for UHD OLED models)
- None

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls, numeric keypad

Keyboard Backlight

LED backlight

UltraNav™

3-button TrackPoint® pointing device and mylar surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)

	-
Models	Dimensions
Touch models	375.4 x 252.3 x 25.25-32.2 mm (14.24 x 9.67 x 0.99-1.27 inches)
Non-touch models	375.4 x 252.3 x 24.5-31.45 mm (14.24 x 9.67 x 0.96-1.24 inches)

Weight[1]

2.74 kg (6.05 lbs)

Case Color



Black

Case Material

PPS695 + GF 50% (top), PPS + GF (bottom)

Notes:

1. The system weight varies depending on configurations

CONNECTIVITY

Network

Onboard Ethernet

- Gigabit Ethernet, Intel Ethernet Connection I219-V (non-vPro models)
- Gigabit Ethernet, Intel Ethernet Connection I219-LM (vPro models)

WLAN + Bluetooth™

- Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card
- No WLAN and Bluetooth

WWAN

- Wireless WAN upgradable to 4G
- Integrated Mobile Broadband 4G LTE-A, Fibocom L860-GL, MIMO 4x4, M.2 card
- No support

SIM Card

No SIM card inbox

NFC

No support

Ports^[1]

Standard Ports^[2]

- 2x USB 3.2 Gen 1 (one Always On)
- 2x USB-C 3.2 Gen 2 / Thunderbolt 3 (support data transfer, Power Delivery and DisplayPort™ 1.4)
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery and DisplayPort 1.4)
- 1x HDMI 2.0
- 1x SD card reader
- 1x Ethernet (RJ-45)
- 1x headphone / microphone combo jack (3.5mm)
- 1x Security keyhole

Optional Ports

- 1x Nano-SIM card slot (WWAN model)
- 1x Smart card reader

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s:

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formely USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formely USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt 3: 40 Gbit/s;

FireWire 400: 400 Mbit/s;

FireWire 800: 800 Mbit/s

2. Depending on many factors, actual data transfer speed may be lower than theoretical speed

Monitor Cable

Monitor Cable

- Lenovo HDMI to VGA Monitor Adapter
- Lenovo USB-C to DisplayPort Adapter
- Lenovo USB-C to VGA Adapter
- No monitor cable

SECURITY & PRIVACY



Security

Security Chip

- · Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset
- Disabled (in some regions)

Physical Locks

Kensington® Security Slot

Smart Card Reader

- · Smart card reader
- No smart card reader

Fingerprint Reader

Touch style fingerprint reader on palm rest, match-on-chip

BIOS Security

- Supervisor password
- Power-on password
- Hard disk password
- Self-healing BIOS

Other Security

- · (Optional) ThinkShutter camera cover
- (Optional) IR camera for Windows Hello

MANAGEABILITY

System Management

System Management

- Intel vPro Technology, DASH
- None

SERVICE

Warranty

Base Warranty

- 1-year depot service
- 1-year depot with 2-year system board service
- 1-year limited onsite service
- 1-year + 2-year depot service
- 1-year + 2-year limited onsite service
- 3-year (1-yr battery) depot service
- 3-year (1-yr battery) limited onsite service
- No base warranty

ENVIRONMENTAL

Operating Environment

Temperature^[2]

- Storage and transportation in original shipping packaging: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)
- Operating: 5°C (41°F) to 35°C (95°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Δltitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

OTO NAME COM



Notes:

- 1. When you charge the battery, its temperature must be no lower than 10°C (50°F)
- 2. When charging the battery pack, the environment temperature must be no lower than 10 % (50 %)

ACCESSORIES

Bundled Accessories

Bundled Accessories

None

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810G military test passed

ISV Certifications

ISV Certifications

Laptop VANG.com Please visit www.thinkworkstations.com/isv-certifications/









