Latitude 7340

Setup and Specifications

LaptopyAMG.com





Notes, cautions, and warnings

i NOTE: A NOTE indicates important information that helps you make better use of your product.

CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

MARNING: A WARNING indicates a potential for property damage, personal injury, or death.

Lapto VANG. com


© 2023 Dell Inc. or its subsidiaries. All rights reserved. Dell Technologies, Dell, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

Contents

3		
•		
• -		
9		
Battery charge and status light		14
	40	
<u> </u>		
·		
. •	<u> </u>	
	<u> </u>	
The state of the s		
· ·		
•		
•		
• • • • • • • • • • • • • • • • • • • •		
g .		
Contacted smart-card reader		27
Operating and storage environment		27
Chapter 4: ComfortView Plus		29
Chapter 5: Keyboard shortcuts of Latitu	de 7340	30
Chapter 6: Getting help and contacting	Dell	32

Set up your Latitude 7340

- i NOTE: The images in this document may differ from your computer depending on the configuration you ordered.
- 1. Connect the power adapter and press the power button.



- NOTE: To conserve battery power, the battery might enter power saving mode. Connect the power adapter and press the power button to turn on the computer.
- 2. Finish operating system setup.

For Ubuntu:

Follow the on-screen instructions to complete the setup. For more information about installing and configuring Ubuntu, search in the Knowledge Base Resource at www.dell.com/support.

For Windows:

Follow the on-screen instructions to complete the setup. When setting up, Dell recommends that you:

- Connect to a network for Windows updates.
 - NOTE: If connecting to a secured wireless network, enter the password for the wireless network access when prompted.
- If connected to the internet, sign-in with or create a Microsoft account. If not connected to the internet, create an
 offline account.

- $\bullet\,$ On the Support and Protection screen, enter your contact details.
- **3.** Locate and use Dell apps from the Windows Start menu—Recommended.

Table 1. Locate Dell apps

Resources	Description
	Dell Product Registration Register your computer with Dell.
	Dell Help & Support Access help and support for your computer.
	SupportAssist
₹	SupportAssist is the smart technology that keeps your computer running at its best by optimizing settings, detecting issues, removing viruses and notifies when you need to make system updates. SupportAssist proactively checks the health of your system's hardware and software. When an issue is detected, the necessary system state information is sent to Dell to begin troubleshooting. SupportAssist is preinstalled on most of the Dell devices running Windows operating system. For more information, see SupportAssist for Home PCs User's Guide on www.dell.com/serviceabilitytools. i NOTE: In SupportAssist, click the warranty expiry date to renew or upgrade your warranty.
	NOTE: In SupportAssist, click the warranty expiry date to renew of upgrade your warranty.
	Dell Update Updates your computer with critical fixes and latest device drivers as they become available. For more information on using Dell Update, search in the Knowledge Base Resource at www.dell.com/
	support.
	Dell Digital Delivery
	Download software applications, which are purchased but not preinstalled on your computer. For more information on using Dell Digital Delivery, search in the Knowledge Base Resource at www.dell.com/support.

Views of Latitude 7340

Right




- 1. Universal audio port
- 2. USB 3.2 Gen 1 port with PowerShare
- 3. Wedge-shaped lock slot

Left



- **1.** HDMI 2.0 port
- 2. Thunderbolt 4 ports with DisplayPort Alt Mode/USB4/Power Delivery
- 3. Thunderbolt 4 ports with DisplayPort Alt Mode/USB4/Power Delivery
- 4. Battery indicator LED

Top



- 1. Dual array microphone
- 2. Camera shutter
- **3.** Power button with fingerprint reader (optional)
- 4. Keyboard
- 5. Speaker
- 6. Clickpad
- 7. Speaker

Display



- 1. IR emitter (optional)
- 2. IR camera (optional)
- 3. RGB camera
- 4. Camera indicator LED
- 5. Ambient Light Sensor (ALS, optional)
- 6. LCD panel


Bottom



- 1. Speakers
- 2. Air vents
- 3. Service Tag and regulatory labels

Service Tag

The service tag is a unique alphanumeric identifier that allows Dell service technicians to identify the hardware components in your computer and access warranty information.



Modes

i NOTE: The following modes are applicable only to Latitude 7340 2-in-1 computers.

Notebook



Tablet



Stand



Tent



Battery charge and status light

The following table lists the battery charge and status light behavior of your Latitude 7340.

Table 2. Battery charge and status light behavior

Power Source	LED Behavior	System Power State	Battery Charge Level
AC Adapter	Off	S0 - S5	Fully Charged
AC Adapter	Solid White	S0 - S5	< Fully Charged
Battery	Off	S0 - S5	11-100%
Battery	Solid Amber (590+/-3 nm)	S0 - S5	< 10%

- S0 (ON) System is turned on.
- S4 (Hibernate) The system consumes the least power compared to all other sleep states. The system is almost at an OFF state, expect for a trickle power. The context data is written to hard drive.
- S5 (OFF) The system is in a shutdown state.

Specifications of Latitude 7340

Dimensions and weight

The following table lists the height, width, depth, and weight of your Latitude 7340.

Table 3. Dimensions and weight

Description Laptop-Mainstream Values		2-in-1	Laptop-Ultralight
Height:			
Front height	16.44 mm (0.64 in.)	16.45 mm (0.65 in.)	16.64 mm (0.64 in.)
Rear height	17.75 mm (0.69 in.)	17.75 mm (0.70 in.)	17.61 mm (0.69 in.)
Width	299 mm (11.77 in.)	299 mm (11.77 in.)	299 mm (11.77 in.)
Depth	213.16 mm (8.39 in.)	213.16 mm (8.39 in.)	212.86 mm (8.38 in.)
Weight (i) NOTE: The weight of your computer depends on the configuration ordered and manufacturing variability.	2.55 lbs. (1.156 kg)	2.86 lbs. (1.297 kg)	2.17 lbs. (0.982 kg)

Processor

The following table lists the details of the processors that are supported by your Latitude 7340.

Table 4. Processor

Description	Option one	Option two	Option three	Option four
Processor type	13 th Generation Intel Core i5-1335U	13 th Generation Intel Core i5-1345U	13 th Generation Intel Core i7-1355U	13 th Generation Intel Core i7-1365U
Processor wattage	15 W	15 W	15 W	15 W
Processor core count	10	10	10	10
Processor thread count	12	12	12	12
Processor speed	0.9 GHz to 4.6 GHz	1.2 GHz to 4.7 GHz	1.2 GHz to 5.0 GHz	1.3 GHz to 5.2 GHz
Processor cache	12 MB	12 MB	12 MB	12 MB
Integrated graphics	Intel Iris X ^e Graphics	Intel Iris X ^e Graphics	Intel Iris X ^e Graphics	Intel Iris X ^e Graphics

Chipset

The following table lists the details of the chipset supported by your Latitude 7340.

Table 5. Chipset

Description	Values
Chipset	Integrated in the processor
Processor	13 th Generation Intel Core i5/i7
DRAM bus width	Dual-channel, 64-bit
Flash EPROM	64 MB
PCle bus	Up to Gen4.0

Operating system

Your Latitude 7340 supports the following operating systems:

- Windows 11 2022H2
- Windows 11 2021H2
- Windows 11 Pro Downgrade (Windows 10 image factory installed)
- Ubuntu 22.04, 64-bit
- Windows 10 CMGE 2022-L

Memory

The following table lists the memory specifications of your Latitude 7340.

Table 6. Memory specifications

Description	Values
Memory slots	On-board memory i NOTE: Not ungradable
Memory type	Dual-channel, LPDDR5
Memory speed	4800 MT/s
Maximum memory configuration	32 GB
Minimum memory configuration	8 GB
Memory configurations supported	 8 GB, Dual-Channel LPDDR5, 4800 MT/s 16 GB, Dual-Channel LPDDR5, 4800 MT/s 32 GB, Dual-Channel LPDDR5, 4800 MT/s

External ports

The following table lists the external ports on your Latitude 7340.

Table 7. External ports

Description	Values
USB ports	 Two Thunderbolt 4 ports with DisplayPort Alt Mode/USB C/USB4/Power Delivery One USB 3.2 Gen 1 port with PowerShare
Audio port	One Universal Audio Jack
Video port/ports	One HDMI 2.0
Media-card reader	Not supported
Power-adapter port	60 W/65 W/100 W adapter USB-C
Security-cable slot	One wedge-shaped security lock slot
Smart Card Reader	Contacted and Contactless + NFC (optional)
SIM slot	NanoSIM slot (optional)

SIM slot	NanoSIM slot (optional)	
Internal slots The following table lists the internal slots of your Latitude 7340. Table 8. Internal slots		
Description	Values	
M.2	 One M.2 2230 slot for solid-state drive One M.2 3042 slot for 4G WWAN card One M.2 3052 slot for 5G WWAN card i) NOTE: To learn more about the features of different types of M.2 cards, search in the Knowledge Base Resource at www.dell.com/support. 	

Wireless module

The following table lists the Wireless Local Area Network (WLAN) module supported on your Latitude 7340.

Table 9. Wireless module specifications

Description	Values
Model number	Intel AX211 (Integrated on system board)
Transfer rate	2400 Mbps
Frequency bands supported	2.40 GHz/5 GHz/6 GHz
Wireless standards	 WiFi 802.11a/b/g Wi-Fi 4 (WiFi 802.11n) Wi-Fi 5 (WiFi 802.11ac)

Table 9. Wireless module specifications (continued)

Description	Values	
	• Wi-Fi 6E (WiFi 802.11ax)	
Encryption	64-bit/128-bit WEP AES-CCMP TKIP	
Bluetooth	Bluetooth wireless card	

Audio

The following table lists the audio specifications of your Latitude 7340.

Table 10. Audio specifications

Description	Values
Audio controller	Realtek ALC3281 with external Amp ALC1309D
Stereo conversion	Supported
Internal audio interface	High definition audio interface
External audio interface	Universal Audio Jack
Number of speakers	Four
Internal-speaker amplifier	Supported
External volume controls	Supported
Speaker output:	
Average speaker output	2 W
Peak speaker output	2.5 W
Subwoofer output	Not supported
Microphone	Dual-array

Storage

This section lists the storage options on your Latitude 7340.

Your computer supports the following storage configurations:

• One M.2 2230 solid-state drive

The M.2 2230 solid-state drive is the primary drive of your computer.

Table 11. Storage specifications

Storage type	Interface type	Capacity
M.2 2230 solid-state drive	PCle NVMe Gen4 x4	256 GB/512 GB/1 TB/2 TB
M.2 2230 solid-state drive, Self- encrypting drive, Opal 2.0	PCle NVMe Gen4 x4	Up to 256 GB

Keyboard

The following table lists the keyboard specifications of your Latitude 7340.

Table 12. Keyboard specifications

Description	Values	
Keyboard type	New Pro 2.5 battery-saving Mini LED backlit keyboard	
Keyboard layout	QWERTY	
Number of keys	United States and Canada: 79 keysUnited Kingdom: 80 keysJapan: 83 keys	
Keyboard size	X=18.05 mm key pitch Y=18.05 mm key pitch	
Keyboard shortcuts	Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key. i NOTE: You can define the primary behavior of the function keys (F1–F12) changing Function Key Behavior in BIOS setup program.	

Camera

The following table lists the camera specifications of your Latitude 7340.

Table 13. Camera specifications

Description	Option one	Option two	Option three
Number of cameras	There is one camera option: • FHD RGB Camera	There is one camera option: • FHD RGB + IR Camera	There is one camera option: • 5M RGB + IR Camera
Camera type	3.8 mm, 1080p at 30 fps, FHD RGB Webcam	3.8 mm, 1080p at 30 fps, FHD RGB+IR Webcam with ALS	4.4 mm, 1080p at 30 fps, 5M RGB+IR Webcam with ALS
Camera location	Front camera	Front camera	Front camera
Camera sensor type	CMOS sensor technology	CMOS sensor technology	CMOS sensor technology
Camera resolution:			
Still image	1920 x 1080 (FHD)	1920 x 1080 (FHD)	2560 x 1920 (5M)
Video	1920 x 1080 (FHD) at 30 fps	1920 x 1080 (FHD) at 30 fps	2560 x 1920 (5M) at 30 fps
Infrared camera resolution:			
Still image	Not supported	640 x 360	640 x 480
Video	Not supported	640 x 360 at 15 fps	640 x 480 at 15 fps
Diagonal viewing angle:			·
Camera	82 degrees	80 degrees	92 degrees
Infrared camera	Not supported	86.6 degrees	77.3 degrees

Clickpad

The following table lists the clickpad specifications of your Latitude 7340.

Table 14. Clickpad specifications

Description	Values
Clickpad resolution:	
Horizontal	>300 dpi
Vertical	
Clickpad dimensions:	
Horizontal	125 mm (4.92 in.)
Vertical	67 mm (2.63 in.)
Clickpad gestures	For more information about clickpad gestures available on Windows, see the Microsoft knowledge base article at support.microsoft.com.

Power adapter

The following table lists the power adapter specifications of your Latitude 7340.

Table 15. Power adapter specifications

Description		tion Option one Option two		Option three
Туре		60 W AC adapter, USB-C	65 W AC adapter, USB-C	100 W AC adapter, USB-C
Pow	ver-adapter dimensions:	0		·
	Height	22.00 mm (0.866 in.)	28.00 mm (1.10 in.)	26.50 mm (4.80 in.)
	Width	66.00 mm (2.598 in.)	51.00 mm (2.01 in.)	60.00 mm (2.36 in.)
	Depth	55.00 mm (2.165 in.)	112.00 mm (4.41 in.)	122.00 mm (4.80 in.)
Wei	ght	0.105 kg (0.231 lbs)	0.201 kg (0.443 lbs)	0.33 kg (0.731 lbs)
Inpu	t voltage	100 VAC - 240 VAC	100 VAC - 240 VAC	100 VAC – 240 VAC
Inpu	t frequency	50 Hz – 60 Hz	50 Hz – 60 Hz	50 Hz – 60 Hz
Inpu	t current (maximum)	1.70 A	1.70 A	1.70 A
Out	put current (continuous)	20 V/3 A15 V/3 A9 V/3 A5 V/3 A	 20 V/3.25 A 15 V/3 A 9 V/3 A 5 V/3 A 	 20 V/5 A 15 V/3 A 9 V/3 A 5 V/3 A
Rated output voltage		20 VDC15 VDC9 VDC5 VDC	20 VDC15 VDC9 VDC5 VDC	20 VDC15 VDC9 VDC5 VDC
Tem	perature range:			·
	Operating	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)
	Storage	-20°C to 70°C (-4°F to 158°F)	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)

Table 15. Power adapter specifications (continued)

Description	Option one	Option two	Option three
	_		_

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

Battery

The following table lists the battery specifications of your Latitude 7340.

Table 16. Battery specifications

Description		Option one	Option two	Option three	Option four
Battery type		2-cell, 38 Wh, lithium ion, ExpressCharge™	3-cell, 57 Wh, lithium ion, ExpressCharge™	2-cell, 38 Wh, lithium ion, Long Lifecycle, ExpressCharge™	3-cell, 57 Wh, lithium ion, Long Lifecycle, ExpressCharge™
Battery voltage)	7.60 VDC	11.40 VDC	7.60 VDC	11.40 VDC
Battery weight (maximum)		0.156 Kg (0.34 lb)	0.227 kg (0.50 lb)	0.156 Kg (0.34 lb)	0.227 kg (0.50 lb)
Battery dimens	ions:				
	Height	6.30 mm (0.24 in.)	6.30 mm (0.24 in.)	6.30 mm (0.24 in.)	6.30 mm (0.24 in.)
	Width	210.97 mm (8.30 in.)	254.8 mm (10.03 in.)	210.97 mm (8.30 in.)	254.8 mm (10.03 in.)
	Depth	79.80 mm (3.10 in.)	79.8 mm (3.10 in.)	79.80 mm (3.10 in.)	79.8 mm (3.10 in.)
Temperature ra	nge:				
	Operatin g	 Charge: 0°C to 45°C (32°F to 113°F) Discharge: 0°C to 70°C (32°F to 158°F) 	 Charge: 0°C to 45°C (32°F to 113°F) Discharge: 0°C to 70°C (32°F to 158°F) 	 Charge: 0°C to 45°C (32°F to 113°F) Discharge: 0°C to 70°C (32°F to 158°F) 	 Charge: 0°C to 45°C (32°F to 113°F) Discharge: 0°C to 70°C (32°F to 158°F)
	Storage	-20°C to 65°C (-4°F to 149°F)	-20°C to 65°C (-4°F to 149°F)	-20°C to 65°C (4°F to 149°F)	-20°C to 65°C (4°F to 149°F)
Battery operati	ng time	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.
Battery chargin (approximate) (i) NOTE: Cor the chargin duration, st end time, a using the D Manager ap For more in about Dell F Manager, se	ntrol g time, art and nd so on well Power oplication. formation	Express Charge Method: • 0 - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours • 16 - 45°C normal express charge • 46 - 50°C maximum allowable charge	Express Charge Method: • 0 - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours • 16 - 45°C normal express charge • 46 - 50°C maximum allowable charge time	Express Charge Method: O - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours 16 - 45°C normal express charge 46 - 50°C maximum	Express Charge Method: O - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours 16 - 45°C normal express charge 46 - 50°C maximum

Table 16. Battery specifications (continued)

Description	Option one	Option two	Option three	Option four
in the Knowledge Base Resource at www.dell.com/ support.	time from 0 to 100% RSOC is 3 hours Standard Charge/ Predominately AC User Charge Method: • 0 - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours • 16 - 50°C maximum allowable charge time from 0 to 100% RSOC is 3 hours Express Charge Boost Charge Method (Fast Charge for Initial 35%): • 16 - 45°C target charge time from 0 to 35% RSOC is 20 mins for Accelerated Charge	from 0 to 100% RSOC is 3 hours Standard Charge/ Predominately AC User Charge Method: • 0 - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours • 16 - 50°C maximum allowable charge time from 0 to 100% RSOC is 3 hours Express Charge Boost Charge Method (Fast Charge for Initial 35%): • 16 - 45°C target charge time from 0 to 35% RSOC is 20 mins for Accelerated Charge	allowable charge time from 0 to 100% RSOC is 3 hours Standard Charge/ Predominately AC User Charge Method: O - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours 16 - 50°C maximum allowable charge time from 0 to 100% RSOC is 3 hours	allowable charge time from 0 to 100% RSOC is 3 hours Standard Charge/ Predominately AC User Charge Method: O - 15°C maximum allowable charge time from 0 to 100% RSOC is 4 hours 16 - 50°C maximum allowable charge time from 0 to 100% RSOC is 3 hours
Coin-cell battery	Supported	Supported	Supported	Supported

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.

CAUTION: Dell recommends that you charge the battery regularly for optimal power consumption. If your battery charge is completely depleted, connect the power adapter, turn on your computer, and then restart your computer to reduce the power consumption.

Display

The following table lists the display specifications of your Latitude 7340.

Table 17. Display specifications

Descri	ption	Option one	Option two	Option three	Option four
Display	type	Full High Definition (FHD)	Full High Definition (FHD)	Full High Definition (FHD) light weight, super low power, ComfortView Plus, Low Blue Light, Battery- saving	Quad High Definition (QHD) 2-in-1, super low power, ComfortView Plus, Low Blue Light, Gorilla® Glass Victus® with DX
Display- technol	•	Wide Viewing Angle (WVA/IPS)	Wide Viewing Angle (WVA/IPS)	Wide Viewing Angle (WVA/IPS)	Wide Viewing Angle (WVA/IPS)
Display- dimensi area):	-panel ons (active				
	Height	178.78 mm (7.03 in.)	178.78 mm (7.03 in.)	178.78 mm (7.03 in.)	178.80 mm (7.03 in.)

Table 17. Display specifications (continued)

Descri	ption	Option one	Option two	Option three	Option four
	Width	286.04 mm (11.26 in.)	286.04 mm (11.26 in.)	286.04 mm (11.26 in.)	286.08 mm (11.26 in.)
	Diagonal	337.31 mm (13.30 in.)	337.31 mm (13.30 in.)	337.31 mm (13.30 in.)	337.36 mm (13.30 in.)
Display- resoluti	-panel native on	1920 x 1200	1920 x 1200	1920 x 1200	2560 x1600
Luminaı	nce (typical)	250 nits	300 nits	400 nits	500 nits
Megapi	xels	2.304	2.304	2.304	4.096
Color ga	amut	45% NTSC	72% NTSC	100% sRGB	100% sRGB
Pixels F	Per Inch (PPI)	170 ppi	170 ppi	170 ppi	227 ppi
Contras	st ratio (typ)	600:1	700:1	1000:1	1200:1
Respon	se time (min)	35 ms	35 ms	35 ms	35 ms
Refresh	n rate	60 Hz	60 Hz	60 Hz	60 Hz
Horizon	ntal view angle	85 degrees (typical)80 degrees (min)	85 degrees (typical) 80 degrees (min)	85 degrees (typical)80 degrees (min)	85 degrees (typical) 80 degrees (min)
Vertical	l view angle	85 degrees (typical)80 degrees (min)	85 degrees (typical)80 degrees (min)	85 degrees (typical)80 degrees (min)	85 degrees (typical) 80 degrees (min)
Pixel pit	tch	0.149 mm	0.149 mm	0.149 mm	0.111 mm
Power (consumption um)	3.25 W	3.50 W	2.90 W	3.62 W
Anti-gla finish	are vs glossy	Anti-glare	Anti-glare	Anti-glare	Anti-reflection
Touch o	options	No	Yes	No	Yes

Fingerprint reader (Optional)

The following table lists the fingerprint-reader specifications of your Latitude 7340.

i NOTE: The fingerprint reader is located on the power button.

Table 18. Fingerprint reader specifications

Description	Option One	Option two
Fingerprint-reader sensor technology	Capacitive	Capacitive
Fingerprint-reader sensor resolution	500 dpi	508 dpi
Fingerprint-reader sensor pixel size	X: 108Y: 88	X: 96Y: 96

Sensor

The following table lists the sensor of your Latitude 7340.

Table 19. Sensor

Sensor support

Accelerometer (ST Micro LIS2DW12TR): On the base (system board) for both laptop and 2-in-1 systems

Accelerometer + Gyro (ST Micro **LSM6DS3USTR** (primary) or **LSM6DSOUSTR** (secondary)): On the hinge-up sensor board for 2-in-1 system

Accelerometer (ST Micro **LNG2DMTR-GP**): On the hinge-up mid-board in Upsell configuration for clamshell system with MIPI RGB+IR camera

Ambient Light Sensor (optional)

E-compass (ST Micro LIS2MDLTR), only for 2-in-1 system

Proximity for SAR compliance (for the WWAN module) Near Field Proximity Sensor

Hall Effect Sensor

GPU—Integrated

The following table lists the specifications of the integrated Graphics Processing Unit (GPU) supported by your Latitude 7340.

Table 20. GPU—Integrated

Controller	Memory size	Processor
Intel Iris X ^e Graphics	Shared system memory	13 th Generation Intel Core i5/i7

Multiple display support matrix

The following table lists the multiple display support matrix for your Latitude 7340.

Table 21. Multiple display support matrix

Graphics Card	Direct Graphics Controller Direct Output Mode	Supported external displays with computer internal display on	Supported external displays with computer internal display off
Intel Iris X ^e Graphics	Not applicable	3	4

Hardware security

The following table lists the hardware security of your Latitude 7340.

Table 22. Hardware security

Hardware security		
Trusted Platform Module (TPM) 2.0 discrete		
FIPS 140-2 certification for TPM		
Trusted Computing Group (TCG) Certification for TPM		
Contacted smart card and Control vault 3		
Contactless smart card, NFC, and Control vault 3		

Table 22. Hardware security (continued)

Hardware security	
SED SSD NVMe, SSD and HDD (Opal and non-Opal) per SDL	
Fingerprint reader in power button tied to Control vault 3	
One wedge-shaped lock slot	
SED (Opal 2.0 only - PCle Interface)	
Windows Hello - Fingerprint Reader (optional)	
Mechanical privacy shutter for camera (only for metal laptops)	

Smart-card reader

Contactless smart-card reader

This section lists the contactless smart-card reader specifications of your Latitude 7340.

Table 23. Contactless smart-card reader specifications

Title	Description	Dell ControlVault 3 contactless smart-card reader with NFC
Felica Card Support	Reader and software capable of supporting Felica contactless cards	Yes
ISO 14443 Type A Card Support	Reader and software capable of supporting ISO 14443 Type A contactless cards	Yes
ISO 14443 Type B Card Support	Reader and software capable of supporting ISO 14443 Type B contactless cards	Yes
ISO/IEC 21481	Reader and software capable of supporting ISO/IEC 21481 compliant contactless cards and tokens	Yes
ISO/IEC 18092	Reader and software capable of supporting ISO/IEC 21481 compliant contactless cards and tokens	Yes
ISO 15693 Card Support	Reader and software capable of supporting ISO15693 contactless cards	Yes
NFC Tag Support	Supports reading and processing of NFC compliant tag information	Yes
NFC Reader Mode	Support for NFC Forum Defined Reader mode	Yes
NFC Writer Mode	Support for NFC Forum Defined Writer mode	Yes
NFC Peer-to-Peer Mode	Support for NFC Forum Defined Peer to Peer mode	Yes
EMVCo Compliant	Compliant with EMVCO smart card standards as posted to www.emvco.com	Yes
EMVCo Certified	Formally certified based on EMVCO smart card standards	Yes

Table 23. Contactless smart-card reader specifications (continued)

Title	Description	Dell ControlVault 3 contactless smart-card reader with NFC
NFC Proximity OS Interface	Enumerates NFP (Near Field Proximity) device for OS to utilize	Yes
PC/SC OS interface	Personal Computer/Smart Card specification for integration of hardware readers into personal computer environments	Yes
CCID driver compliance	Common driver support for Integrated Circuit Card Interface Device for OS level drivers	Yes
Windows Certified	Device certified by Microsoft WHCK	Yes
Dell ControlVault support	Device connects to Dell ControlVault for usage and processing	Yes
FIDO2 compliance	Dell ControlVault 3 Smart-card reader is compliant with the FIDO SPEC	No

(i) NOTE: 125 Khz proximity cards are not supported.

Table 24. Supported cards

Table 24. Supported cards		
Manufacturer	Card	
HID	jCOP readertest3 A card (14443a)	
	1430 1L	
	DESFire D8H	
	iClass (Legacy)	
	iClass SEOS	
NXP/Mifare	Mifare DESFire 8K White PVC Cards	
	Mifare Classic 1K White PVC Cards	
	NXP Mifare Classic S50 ISO Card	
G&D	idOnDemand - SCE3.2 144K	
	SCE6.0 FIPS 80K Dual+ 1 K Mifare	
	SCE6.0 nonFIPS 80K Dual+ 1 K Mifare	
	SCE6.0 FIPS 144K Dual + 1K Mifare	
	SCE6.0 nonFIPS 144K Dual + 1 K Mifare	
	SCE7.0 FIPS 144K	
Oberthur	idOnDemand - OCS5.2 80K	
	ID-One Cosmo 64 RSA D V5.4 T=0 card	

Contacted smart-card reader

The following table lists the contacted smart-card reader specifications of your Latitude 7340.

Table 25. Contacted smart-card reader specifications

Title	Description	Dell ControlVault 3 smart-card reader
ISO 7816 -3 Class A Card Support	Reader capable of reading 5V powered smart mcard	Yes
ISO 7816 -3 Class B Card Support	Reader capable of reading 3V powered smart card	Yes
ISO 7816 -3 Class C Card support	Reader capable of reading 1.8V powered smart card	Yes
ISO 7816-1 Compliant	Specification for the reader	Yes
ISO 7816 -2 Compliant	Specification for smart card device physical characteristics (size, location of connection points, etc.)	N/A
T=0 support	Cards support character level transmission	Yes
T=1 support	Cards support block level transmission	Yes
EMVCo Compliant	Compliant with EMVCo (for electronic payment standards) smart card standards as posted to www.emvco.com	Yes
EMVCo Certified	Formally certified based on EMVCO smart card standards	Yes
PC/SC OS interface	Personal Computer/Smart Card specification for integration of hardware readers into personal computer environments	Yes
CCID driver compliance	Common driver support for Integrated Circuit Card Interface Device for OS level drivers.	Yes
Windows Certified	Device certified by WHCK	Yes
FIPS 201 (PIV/HSPD-12) Compliant via GSA	Device compliant with FIPS 201/PIV/ HSPD-12 requirements	Yes
FIDO2 compliance	Dell ControlVault 3 Smart-card reader is compliant with the FIDO SPEC	No

Operating and storage environment

This table lists the operating and storage specifications of your Latitude 7340.

 $\textbf{Airborne contaminant level:} \ \ \textbf{G1} \ \ \text{as defined by ISA-S71.04-1985}$

Table 26. Computer environment

Description	Operating	Storage
Temperature range	0°C to 35°C (32°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)*	0.66 GRMS	1.30 GRMS

Table 26. Computer environment (continued)

Description	Operating	Storage
Shock (maximum)	110 G†	160 G†
Altitude range	· · · · · · · · · · · · · · · · · · ·	-15.2 m to 10668 m (4.64 ft to 19234.4 ft)

CAUTION: Operating and storage temperature ranges may differ among components, so operating or storing the device outside these ranges may impact the performance of specific components.



 $[\]ensuremath{^{*}}$ Measured using a random vibration spectrum that simulates user environment.

[†] Measured using a 2 ms half-sine pulse.

ComfortView Plus

WARNING: Prolonged exposure to blue light from the display may lead to long-term effects such as eye strain, eye fatigue, or damage to the eyes.

Blue light is a color in the light spectrum which has a short wavelength and high energy. Chronic exposure to blue light, particularly from digital sources, may disrupt sleep patterns and cause long-term effects such as eye strain, eye fatigue, or damage to the eyes.

The display on this computer is designed to minimize blue light and complies with TÜV Rheinland's requirement for low blue light displays.

Low blue light mode is enabled at the factory, so no further configuration is necessary.

To reduce the risk of eye strain, it is also recommended that you:

- Position the display at a comfortable viewing distance between 20 and 28 inches (50 and 70 cm) from your eyes.
- Blink frequently to moisten your eyes, wet your eyes with water, or apply suitable eye drops.
- Look away from your display, and gaze at a distant object at 20 ft (609.60 cm) away for at least 20 seconds during each , aptopy AMG, cord
- Take an extended break for 20 minutes every two hours.

Keyboard shortcuts of Latitude 7340

NOTE: Keyboard characters may differ depending on the keyboard language configuration. Keys used for shortcuts remain the same across all language configurations.

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. The symbol shown on the lower part of the key refers to the character that is typed out when the key is pressed. If you press shift and the key, the symbol shown on the upper part of the key is typed out. For example, if you press **2**, **2** is typed out; if you press **Shift** + **2**, **@** is typed out.

The keys F1-F12 at the top row of the keyboard are function keys for multi-media control, as indicated by the icon at the bottom of the key. Press the function key to invoke the task represented by the icon. For example, pressing F1 mutes the audio (refer to the table below).

However, if the function keys F1-F12 are needed for specific software applications, multi-media functionality can be disabled by pressing \mathbf{Fn} + \mathbf{Esc} . Subsequently, multi-media control can be invoked by pressing \mathbf{Fn} and the respective function key. For example, mute audio by pressing \mathbf{Fn} + $\mathbf{F1}$.

NOTE: You can also define the primary behavior of the function keys (F1–F12) by changing **Function Key Behavior** in BIOS setup program.

Table 27. List of keyboard shortcuts

Function law		
Function key	Primary behavior	
F1	Mute audio	
F2	Decrease volume	
F3	Increase volume	
F4	Play previous track/chapter	
F5	Play/Pause	
F6	Play next track/chapter.	
F8	Switch to external display	
F9	Search	
F10	Click keyboard backlight (optional). NOTE: Non-backlight keyboards have F10 function key without the backlight icon and do not support toggle keyboard backlight function. NOTE: Toggle to cycle the keyboard backlight status through off, low-backlight, and high-backlight	
F11	Decrease brightness	
F12	Increase brightness	

The Fn key is also used with selected keys on the keyboard to invoke other secondary functions.

Table 28. Secondary behavior

Function key	Secondary behavior
Fn + F1	Operating system and application specific F1 behavior
Fn + F2	Operating system and application specific F2 behavior
Fn + F3	Operating system and application specific F3 behavior
Fn + F4	Operating system and application specific F4 behavior

Table 28. Secondary behavior (continued)

Function key	Secondary behavior
Fn + F5	Operating system and application specific F5 behavior
Fn + F6	Operating system and application specific F6 behavior
Fn + F8	Operating system and application specific F8 behavior
Fn + F9	Operating system and application specific F9 behavior
Fn + F10	Operating system and application specific F10 behavior
Fn + F11	Operating system and application specific F11 behavior
Fn + F12	Operating system and application specific F12 behavior
Fn + PrtScr	Turn off/on wireless
Fn + B	Pause/Break
Fn + Insert	Sleep
Fn + S	Toggle scroll lock
Fn + H	Toggle between power and battery-status light/hard-drive activity light
Fn + R	System request
Fn + Ctrl	Open application menu
Fn + Esc	Toggle Fn-key lock
Fn + PgUp	Page up
Fn + PgDn	Page down
Fn + Home	Home
Fn + End	End

Getting help and contacting Dell

Self-help resources

You can get information and help on Dell products and services using these self-help resources:

Table 29. Self-help resources

Self-help resources	Resource location
Information about Dell products and services	www.dell.com
My Dell app	DELL
Tips	· ·
Contact Support	In Windows search, type Contact Support, and press Enter.
Online help for operating system	www.dell.com/support/linux
Access top solutions, diagnostics, drivers and downloads, and learn more about your computer through videos, manuals and documents.	Your Dell computer is uniquely identified by a Service Tag or Express Service Code. To view relevant support resources for your Dell computer, enter the Service Tag or Express Service Code at www.dell.com/support. For more information on how to find the Service Tag for your computer, see Locate the Service Tag on your computer.
Dell knowledge base articles for a variety of computer concerns	 Go to www.dell.com/support. On the menu bar at the top of the Support page, select Support > Knowledge Base. In the Search field on the Knowledge Base page, type the keyword, topic, or model number, and then click or tap the search icon to view the related articles.

Contacting Dell

To contact Dell for sales, technical support, or customer service issues, see www.dell.com/contactdell.

- (i) NOTE: Availability varies by country/region and product, and some services may not be available in your country/region.
- NOTE: If you do not have an active Internet connection, you can find contact information about your purchase invoice, packing slip, bill, or Dell product catalog.