OVERVIEW

1. USB-C 3.2 Gen 1	5. microSD card reader
2. HDMI	6. USB 3.2 Gen 1
3. USB-C 3.2 Gen 1	7. USB 3.2 Gen 1 (Always On)
4. Headphone / microphone combo jack (3.5mm)	

PERFORMANCE

Processor

Processor Family

13th Generation Intel[®] U, P, H Series Core[™] i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics
Core™ i5- 1335U	10 (2 P-core + 8 E-core)	12	P-core 1.3GHz / E-core 0.9GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® Iris® Xe Graphics
Core™ i5- 1340P	12 (4 P-core + 8 E-core)	16	P-core 1.9GHz / E-core 1.4GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® Iris® Xe Graphics
Core™ i5- 13420H	8 (4 P-core + 4 E- core)	12	P-core 2.1GHz / E-core 1.5GHz	P-core 4.6GHz / E-core 3.4GHz	12MB	Intel® UHD Graphics
Core™ i5- 13500H	12 (4 P-core + 8 E-core)	16	P-core 2.6GHz / E-core 1.9GHz	P-core 4.7GHz / E-core 3.5GHz	18MB	Intel® Iris® Xe Graphics
Core™ i7- 1355U	10 (2 P-core + 8 E-core)	12	P-core 1.7GHz / E-core 1.2GHz	P-core 5.0GHz / E-core 3.7GHz	12MB	Intel® Iris® Xe Graphics
Core™ i7- 1360P	12 (4 P-core + 8 E-core)	16	P-core 2.2GHz / E-core 1.6GHz	P-core 5.0GHz / E-core 3.7GHz	18MB	Intel® Iris® Xe Graphics
Core™ i7- 13620H	10 (6 P-core + 4 E-core)	16	P-core 2.4GHz / E-core 1.8GHz	P-core 4.9GHz / E-core 3.6GHz	24MB	Intel® UHD Graphics
Core™ i7- 13700H	14 (6 P-core + 8 E-core)	20	P-core 2.4GHz / E-core 1.8GHz	P-core 5.0GHz / E-core 3.7GHz	24MB	Intel® Iris® Xe Graphics
Operating System						
Operating Syste	m**					
			node			

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows[®] 11 Home Single Language
- Windows® 11 Home Single Language in S mode
- Windows[®] 11 Home in S mode
- No preload operating system

Graphics

Graphics**

Graphics	Туре	Memory	Key Features
Intel [®] UHD Graphics	Integrated	Shared	DirectX® 12.1
Intel [®] Iris [®] Xe Graphics ^[1]	Integrated	Shared	DirectX® 12.1

Notes:

[1] Intel® Iris® Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel® Iris® Xe Graphics will function as Intel® UHD Graphics.

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 1920x1080@60Hz
- USB-C[®] supports up to 3840x2160@60Hz

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots, single-channel (8GB models)
- Memory soldered to systemboard, no slots, dual-channel (16GB models)

Memory Type

LPDDR5-5200

Storage

Storage Support^[1]

One drive, up to 1TB M.2 2242 SSD or 1TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe® 4.0 x4 slot

Storage Type**

Disk Type	Interface	Offering
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	1TB
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

PLODAL

Removable Storage

Card Reader

microSD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

Stereo speakers, 2W x2, optimized with Dolby[®] Audio™

Microphone

Dual-microphone array

Camera*

- FHD 1080p + IR, with privacy shutter, fixed focus, with ToF sensor
- FHD 1080p, with privacy shutter, fixed focus

Sensor

Sensors

- (Optional) Ambient light sensor (ALS)
- (Optional) ToF sensor
- Hall sensor

Battery

Battery**

- Integrated Li-Polymer 56.6Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)[1]
- Integrated Li-Polymer 75.4Wh battery, supports Rapid Charge Boost (get 2 hours of runtime with a 15-minute charge)^[2]

Max Battery Life^[3]

- 56.6Wh (Core™ i5 U-Series with WUXGA panel models): MobileMark[®] 2018@200nits: 11.5 hr Local video (1080p) playback@150nits: 14.5 hr
- 56.6Wh (Core™ i5 P-Series with WUXGA panel models):

MobileMark® 2018@200nits: 9.5 hr Local video (1080p) playback@150nits: 14.5 hr

- 56.6Wh (Core[™] i5 H-Series with WUXGA panel models): MobileMark[®] 2018@200nits: 8.8 hr Local video (1080p) playback@150nits: 11.5 hr
- 56.6Wh (Core™ i7 P-Series with 2.5K panel models): MobileMark[®] 2018@200nits: 10 hr Local video (1080p) playback@150nits: 15.5 hr
- 75.4Wh (Core™ i5 P-Series with WUXGA panel models): MobileMark[®] 2018@200nits: 13 hr
- Local video (1080p) playback@150nits: 18 hr
 75.4Wh (Core™ i5 H-Series with 2.5K panel models): MobileMark[®] 2018@200nits: 13 hr
- Local video (1080p) playback@150nits: 17.6 hr
 75.4Wh (Core™ i7 U-Series with 2.5K panel models): MobileMark® 2018@200nits: 15.5 hr Local video (1080p) playback@150nits: 17 hr
- 75.4Wh (Core™ i7 P-Series with 2.5K panel models): MobileMark[®] 2018@200nits: 14 hr Local video (1080p) playback@150nits: 20.5 hr

Notes:

[1], [2] Rapid Charge Boost is only effective in hibernates or fully shutting down the computer.

[3] All battery life claims are approximate maximum and based on results using the MobileMark[®] 2014, MobileMark[®] 2018, MobileMark[®] 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 65W USB-C[®] (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C[®] slim (wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 100W USB-C[®] slim (3-pin) AC adapter, supports PD 30, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
16″	WUXGA (1920x1200)	None	IPS	300nits	Anti- glare	16:10	1000:1	45% NTSC	60Hz	85°/85°/85°/85°	TÜV Low Blue Light (Software)
16″	WUXGA (1920x1200)	Multi- touch	IPS	300nits	Anti- glare	16:10	1000:1	45% NTSC	60Hz	85°/85°/85°/85°	TÜV Low Blue Light (Software)
16″	2.5K (2560x1600)	None	IPS	350nits	Anti- glare	16:10	1200:1	100% sRGB	60Hz	85°/85°/85°/85°	Dolby® Vision™, TÜV Low Blue Light (Hardware)

Touchscreen

• On-cell multi-touch, supports 10-point touch

Non-touch

Lenovo

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

- LED backlight
- Non-backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)^[1]

Models	Dimensions				
Metal models	356 x 251 x 16.9 mm (14.02 x 9.88 x 0.67 inches)				
Plastic models	356 x 251 x 17.9 mm (14.02 x 9.88 x 0.70 inches)				

Weight^[2]

Starting at 1.89 kg (4.17 lbs)

Case Color**

- Abyss blue
- Cloud grey
- Violet

Surface Treatment

Aluminium stamping (anodized with sandblasting)

Case Material**

- Aluminium (top), PC-ABS (bottom)
- Aluminium (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo[®] lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

iopyance.com

CONNECTIVITY

Network

Ethernet

No onboard Ethernet

WLAN + Bluetooth®**

- Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card^[1]
- Wi-Fi[®] 6E, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card^[2]

Notes:

[1] Wi-Fi[®] 6 full features might be limited by country-level restrictions.

[2] Wi-Fi[®] 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Ports^D

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)

Lenovo

- 2x USB-C[®] 3.2 Gen 1 (support data transfer, Power Delivery 3.0 and DisplayPort[™] 1.4)
- 1x HDMI® 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x microSD card reader

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4[®] 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4[®] 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

Docking

Docking

Various docking solutions are supported via USB-C[®]. For more compatible docking solutions, please visit Docking for IdeaPad® Slim 5 16IRL8

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

- aptopy ANG. com Touch style fingerprint reader on palm rest
- No fingerprint reader

BIOS Security

- Administrator password
- User password
- Master hard disk password
- User hard disk password
- Self-healing BIOS

Other Security

- (Optional) IR camera for Windows® Hello (facial recognition)
- Camera privacy shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft) - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F) At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Lenovo

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

None

Notes:

[1] For more compatible accessory solutions, please visit Accessories for IdeaPad® Slim 5 16IRL8.

CERTIFICATIONS

Green Certifications⁽¹⁾

Green Certifications^[2]

- ENERGY STAR® 8.0
- EPEAT[™] Gold Registered^[3]
- ErP Lot 6
- ErP Lot 26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications' section may not only refer to certification but also registration or selfdeclaration.

NANG. COM

[2] EPEAT™ registration and ENERGY STAR[®] certification are dependent on system OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT[™] is registered where applicable, please see epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed (20 test items)

Other Certifications

- (Optional) TÜV Rheinland[®] Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)
- TÜV Rheinland® Flicker Free
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without

notice.

Laptopymyc.com







